


Order No.: 5XA7662A1A1AC | GTIN (EAN): 4058352220139

Product description: FL20mc,PL43,LED2550lm830,Plus,bracket



4058352220139
5XA7662A1A1AC
LED 3000K / CRI ≥ 80



Floodlight 20 micro LED, floodlight, LED unit, primary light control with lens, of plastic, primary optical cover: protective disc, of toughened safety glass, transparent, light distribution: PL43, light emission: direct distribution, installation type: surface-mounted, LED, LED High Power, rated luminous flux: 2.550lm, luminous efficacy: 95lm/W, light colour: 830, colour temperature: 3000K, control gear: ECG Plus, control: flexible luminous flux parameterisation, time-dependent luminous flux control, digital communication interface, power reduction, overheat protection, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, 50/60Hz, rated input power: 27W, LED unit, luminaire module, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 304mm, width: 222mm, height: 55mm, housing frame, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), mounting bracket, of steel, powder-coated, Siteco® metallic grey (DB 702S), DALI, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, protection symbol: D, permissible operating ambient temperature: -40..+40°C, permissible operating ambient temperature for outdoor applications: -40..+50°C, standard: DIN EN 12944, packaging unit: 1 piece



Lamps: LED
Wt. (kg): 3.4
GTIN (EAN): 4058352220139

5XA7662A1A1AC

The luminaire contains built-in LED lamps

A++
A+
A
B
C
D
E

LED
D

The LED-lamps cannot be changed in the luminaire

874/2012

