



Order No.: 5XA7662A1C1AC | GTIN (EAN): 4058352220238

Product description: FL20mc,PL61,LED2430lm830,Plus,bracket



4058352220238
5XA7662A1C1AC

LED 3000K / CRI ≥ 80 Φ_{H} 2430 lm



Floodlight 20 micro LED, floodlight, LED unit, primary light control with lens, of plastic, primary optical cover: protective disc, of toughened safety glass, transparent, light distribution: PL61, light emission: direct distribution, installation type: surface-mounted, LED, LED High Power, rated luminous flux: 2.430lm, luminous efficacy: 91lm/W, light colour: 830, colour temperature: 3000K, control gear: ECG Plus, control: flexible luminous flux parameterisation, time-dependent luminous flux control, digital communication interface, power reduction, overheat protection, electronic power reduction, with terminal, 5-pole, max. 2.5mm², mains connection: 220..240V, AC, 50/60Hz, rated input power: 27W, LED unit, luminaire module, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), length: 304mm, width: 222mm, height: 55mm, housing frame, of diecast aluminium, powder-coated, Siteco® metallic grey (DB 702S), mounting bracket, of steel, powder-coated, Siteco® metallic grey (DB 702S), DALI, protection rating (complete): IP66, insulation class (complete): insulation class II (safety insulation), certification: CE, ENEC, VDE, protection symbol: D, permissible operating ambient temperature: -40..+40°C, permissible operating ambient temperature for outdoor applications: -40..+50°C, standard: DIN EN 12944, packaging unit: 1 piece



| | |
|-------------|---------------|
| Lamps: | LED |
| Wt. (kg): | 3.4 |
| GTIN (EAN): | 4058352220238 |

5XA7662A1C1AC

The luminaire contains built-in LED lamps

A++

A+

A

B

C

D

E

LED

The LED-lamps cannot be changed in the luminaire

874/2012

